

ITEM	QTY	LENGTH (mm)	COLOUR	DESCRIPTION
Universal Connector (KT-P-002)	44	Kwiktech Ultimate DIY Shed Kit		
Rail Connector (KT-P-003)	40			
60° Rail Connector (KT-P-004)	4			
M6 x 40mm Zinc Plated Socket Head Cap Screw	44			
10g x 16mm Self-Drilling Galvanised Wafer Head Screw	275			
Right Angle Bracket	5			

NOTE: BOM refers to door front (door position 1) & fitted to existing concrete footings

ITEM	QTY	LENGTH (mm)	COLOUR	DESCRIPTION
SHS 50X50X1.5	2	2375	Galv	Front Posts
SHS 50X50X1.5	2	1767	Galv	Back Posts
SHS 50X50X1.5	1	2326	Galv	Door Housing Post
SHS 50X50X1.5	2	3125	Galv	Roof Members
SHS 50X50X1.5	2	2040	Galv	Door Frame Vertical Posts
RHS 38X25X1.2	1	820	Galv	Door Housing Horizontal Member
RHS 38X25X1.2	1	2242	Galv	Front Diagonal Brace
RHS 38X25X1.2	1	2070	Galv	Front Horizontal Member
RHS 38X25X1.2	4	3217	Galv	Diagonal Bracings
RHS 38X25X1.2	7	2970	Galv	Horizontal Members
RHS 38X25X1.2	2	74	Galv	Front Roof Tie Bracings
RHS 38X25X1.2	2	85	Galv	Back Roof Tie Bracings
RHS 38X25X1.2	3	705	Galv	Door Frame Horizontal Members
RHS 38X25X1.2	1	1355	Galv	Door Frame Diagonal Brace
Cladding – TrimDek 762X28	3	2426	Monument	Front
Cladding – TrimDek 762X28	4	1803	Monument	Back
Cladding – TrimDek 762X28	2	2416	Monument	Sides
Cladding – TrimDek 762X28	2	2264	Monument	Sides
Cladding – TrimDek 762X28	2	2112	Monument	Sides

ITEM	QTY	LENGTH (mm)	COLOUR	DESCRIPTION
Cladding – TrimDek 762X28	2	1961	Monument	Sides
Cladding – TrimDek 762X28	4	3270	Monument	Roof
Cladding – TrimDek 762X28	1	371	Monument	Top of Door Section
Cladding – TrimDek 762X28	1	2038	Monument	Door
65X65 Flashing Bend 79°	1	3200	Monument	Peak of Shed Flashing – Refer Drawing
65X65 Flashing Bend 90°	2	3270	Monument	Roof Sides
65X65 Flashing Bend 90°	2	2450	Monument	Front Sides
65X65 Flashing Bend 90°	2	1840	Monument	Back Sides
40X40 Flashing Bend 90°	1	900	Monument	Door Top
50X15 Flashing Bend 90°	1	2050	Monument	Door Frame Housing – Cladding Side
65X65 Flashing Bend 90°	2	835	Monument	Door Top & Bottom
Under Flashing - Folded to suit Drawing	1	2900	Galv	1.2mm Sheet folded - Back Flashing - Refer Drawing
75X3 Flat Bar	1	3000	Galv	Door Stop (Fitted to inside of Door Housing Post)
Door Hinge	2	-	Galv	Heavy Duty with Steel Fixing Screws
Door Handle (Tee Handle) Lockable with Key - fixings included	1	-	Black	Fit(drill) Through Door Frame Mid Horizontal Member
Tee Handle Lever/Tongue (which attaches to Door Handle)	1	-	Galv	Locks Door from Inside against Door Stop
Base Plates	5	-	Galv	Corner shape (L Shape) to suit 50X50 Posts
Dynabolts M10X50	10	M10X50	Galv	X2 per Base Plate
Tek Screw 10X16mm With Neo	300	10X16mm	Monument	Colour to match Monument as best as practicable
Tek Screw 12X50mm Zip with Neo (M&T) Tornado	100	12X50mm	Monument	Colour to match Monument as best as practicable

NOTES: Ensure all footings are level. Some Cladding and Flashings will require trimming upon installation. Fix Cladding to Diagonal Bracings upon installation.

Visit www.kwiktech.com.au for Video Tutorials and Download Information Sheets